

SPECIFICATION SUBMITTAL

Project: _____
 Architect/Engineer: _____
 Builder/Developer: _____
 Plumbing Contractor: _____



FlowTite® 4ALL®

FOR PEX, COPPER & CPVC



One Valve Fits ALL

FlowTite® 4ALL® Oil Rubbed Bronze Supply Stop Valve / Factory Attached One-Piece Double Layer Flexible Reinforced Braided Connector System - For Copper, CPVC and PEX Pipe

Model Number	Description
<input type="checkbox"/> P05B-3,2 (XF-XC)	Valve-Only: 1/2" Nominal Supply Stop Valves With 3/8" or 1/4" O.D. Compression Nut.
<input type="checkbox"/> P05LB-5,3 (XP-XF-XC-XL-XE)	One-Piece: Factory Attached Flexible Braided Connector for Faucets and Dishwashers.
<input type="checkbox"/> P05CB-7 (XF)	One-Piece: Factory Attached Flexible Braided Connector for Toilets.
<input type="checkbox"/> P05IB-2 (F-T)	One-Piece: Factory Attached Flexible Braided Connector for Ice Makers.



1/2" IPS



7/8" Ballcock



3/8" Comp. Adapter (w/ nut)



1/4" Comp.



3/8" Comp. Adapter (w/o nut)



3/8" Brass Elbow



3/8" x 3/4" Whirlpool Elbow

Design Features / Benefits

- 10 year limited warranty including labor and material for residential and one year for commercial.
 - Property owner protection.
 - Reduced maintenance costs.
- Tested to 1,000 psi.
 - 10:1 margin of safety.
- Over 35 million **PUSHON** technology valve installations in over 2.5 million new U.S. homes since 1988.
 - Long-term proven technology performance.
- Easy Pull/Push ON/OFF Handle.
 - No sticking or leaking turn handles due to dried out rubber packing.
- Original one-piece factory attached double reinforced connector.
 - Maximum abuse resistance.
 - Eliminates potential leaks at joints.
- 100% non-metallic water contact.
 - No lead, no internal corrosion, no brass dezincification.
- NSF certified lead free.
 - Health Safe.
- Clean look.
 - To fit any interior.
- Removable and Reusable.
 - Installation does not damage pipe.

Listings:

For product specific listings please refer to NSF and IAPMO websites.