

# SPECIFICATION SUBMITTAL

Project: \_\_\_\_\_  
 Architect/Engineer: \_\_\_\_\_  
 Builder/Developer: \_\_\_\_\_  
 Plumbing Contractor: \_\_\_\_\_



FOR PEX, COPPER & CPVC



Valve Only Model  
 (OBP05-2, VBPO5-2, XBP05-2)



One Piece Valve/Riser Model  
 (OBPO5-IS-2, VBPO5-IS-2, XBP05-IS-2)



Valve Only w/ Arrester Model  
 (OBPO5-2A, VBPO5-2A, XBP05-2A)

## Listings:

NSF/ANSI 61  
 IAPMO File 2657 (cUPC/IPC/NPC of Canada)  
 IAPMO File 6518 (Lead Free)  
 IAPMO File 3893 (Outlet Boxes)

## Manufactured in accordance with:

NSF/ANSI 61 Section 9 Certified  
 ASME A112.18.1/CSA B125.1  
 Section 1417(d) US SDWA and NSF/ANSI 372  
 IAPMO PS 54

## PUSHON® Ice Maker Outlet Box with White Supply Stop Valve / Factory Attached One-Piece High Performance™ Double Layer Flexible Reinforced Braided Connector System

Model Number	Description
<input type="checkbox"/> OBP05-2 (Copper)	Round high impact polystyrene box with factory installed PUSHON PEX valve (1/2" x 1/4" comp. outlet) for Copper, CPVC or PEX pipe. Face-plate included. Metal insert sleeve (not included) required if poly tubing is used for ice maker connection. Protective cover optional.
<input type="checkbox"/> VBPO5-2 (CPVC)	
<input type="checkbox"/> XBP05-2 (PEX)	
<input type="checkbox"/> *OBPO5-2A (Copper)	
<input type="checkbox"/> *VBPO5-2A (CPVC)	* Factory installed arrester.
<input type="checkbox"/> *XBP05-2A (PEX)	
<input type="checkbox"/> OBP05-IS-2 (Copper)	
<input type="checkbox"/> VBPO5-IS-2 (CPVC)	Round high impact polystyrene box with factory installed PUSHON PEX valve and 84" High Performance reinforced braided connector x 1/4" comp. nut. For Copper, CPVC or PEX pipe. Face-plate included and protective cover included.
<input type="checkbox"/> XBP05-IS-2 (PEX)	
<input type="checkbox"/> *OBPO5-IS-2 (Copper)	
<input type="checkbox"/> *VBPO5-IS-2 (CPVC)	
<input type="checkbox"/> *XBP05-IS-2 (PEX)	* Factory installed arrester.

## Design Features / Benefits

- Unique round design.
  - Strong and durable.
  - No need to level like rectangular or square boxes which eliminates call backs.
- Six tough support nailing tabs for ease of installation and superior support strength.
  - Install in any direction (up, down or sideways).
  - Three tabs on each side provide more support on the stud.
- Movable nailing brackets included for additional support when needed.
  - Brackets for additional support behind the stud or to support additional bracing if necessary for 2 x 4 or 2 x 6 walls.
- Protective cover included on models with one piece valve/riser. Optional on valve-only models.
  - Protects valve and riser from paint and dirt during rough-in stage.
- FlowTite box, valve and connectors are one integral unit.
  - One piece design eliminates the "gray area" of responsibility for the hookup from the ice maker valve to the appliance. 100% factory air tested.
- Clean look for the builder and owner.
  - Non-corrosive, no rust, high tech look.
- Long term owner protection.
  - Health safe NSF61 material with written 10 year labor and material warranty.
- Reduced maintenance cost.
  - Valves are removable by twisting counter-clockwise.