

SPECIFICATION SUBMITTAL

Project: _____
 Architect/Engineer: _____
 Builder/Developer: _____
 Plumbing Contractor: _____



FlowTite®



FlowTite® “HP Series” Lead Free High Performance™ Flexible Reinforced Braided Connectors for Faucets, Toilets, Dishwashers and Ice Makers - For use in accessible locations only

Design Features

- Quality made in U.S.A. since 1988
- Hydraulic machine crimped stainless steel ferrules
- EPDM rubber seals
- NSF/ANSI 61 Section 9 Certified
- IAPMO Certified Lead Free
- High performance flexible connectors with dual layer protection built in using durable polymer braid over reinforced PVC

Faucet Connections Example: 3/8" Female Comp. nut Stop End x 1/2" Polymer IPS nut Fixture End x 20" Length = RLS20-5PF

- | Stop Valve End: | Fixture End: | Available Lengths: |
|--|---|---|
| <input type="checkbox"/> 1/2" Polymer IPS nut (R5LS) | <input type="checkbox"/> 1/2" Polymer IPS nut (5PF) | <input type="checkbox"/> 6" <input type="checkbox"/> 9" <input type="checkbox"/> 12" <input type="checkbox"/> 15" |
| <input type="checkbox"/> 3/8" Female comp. nut (RLS) | <input type="checkbox"/> 3/8" Female comp. nut (3F) | <input type="checkbox"/> 20" <input type="checkbox"/> 24" <input type="checkbox"/> 30" <input type="checkbox"/> 36" |
| | <input type="checkbox"/> 3/8" Male comp./thread nut (3CF) | |

Toilet Connections Example: 3/8" Female Comp. nut Stop End x 7/8" Ballcock nut Fixture End x 12" Length = RCS12-7F

- | Stop Valve End: | Fixture End: | Available Lengths: |
|--|---|--|
| <input type="checkbox"/> 3/8" Female comp. nut (RCS) | <input type="checkbox"/> 7/8" Ballcock nut (7F) | <input type="checkbox"/> 9" <input type="checkbox"/> 12" <input type="checkbox"/> 15" <input type="checkbox"/> 20" |
| <input type="checkbox"/> 1/2" Polymer IPS nut (R5CS) | | |

Dishwasher Connections Example: 3/8" Female Comp. nut Stop End x 3/8" Brass Elbow Appliance End x 84" Length = RLS84-3EL

- | Stop Valve End: | Appliance End: | Available Lengths: |
|--|---|---|
| <input type="checkbox"/> 3/8" Female comp. nut (RLS) | <input type="checkbox"/> 3/8" Female comp. nut (3E) | <input type="checkbox"/> 48" <input type="checkbox"/> 60" <input type="checkbox"/> 72" <input type="checkbox"/> 84" |
| <input type="checkbox"/> 1/2" Polymer IPS nut (R5LS) | <input type="checkbox"/> 3/8" Brass Elbow (3EL) | <input type="checkbox"/> 120" <input type="checkbox"/> 144" |
| | <input type="checkbox"/> 3/8" x 3/4" Whirlpool Elbow (3WEL) | |
| | <input type="checkbox"/> 1/2" Polymer IPS nut (5PF) | |

Ice Maker Connections Example: 1/4" Comp. nut Stop End x 1/4" Comp. nut Appliance End x 84" Length = R2IS84-2F

- | Stop Valve End: | Appliance End: | Available Lengths: |
|--|--|---|
| <input type="checkbox"/> 1/4" comp. nut (R2IS) | <input type="checkbox"/> 1/4" comp. nut (2F) | <input type="checkbox"/> 48" <input type="checkbox"/> 60" <input type="checkbox"/> 72" <input type="checkbox"/> 84" |

Listings:

NSF/ANSI 61
 IAPMO File 3969 (UPC/IPC)
 IAPMO File 6518 (Lead Free)

Manufactured in accordance with:

NSF/ANSI 61 Section 9 Certified
 ASME A112.18.6/CSA B125.6
 NSF/ANSI 372 and US SDWA



1/2" IPS



7/8" Ballcock



3/8" Comp. Adapter (w/ nut)



1/4" Comp. Adapter



3/8" Comp. Adapter (w/o nut)



3/8" Brass Elbow



3/8" x 3/4" Whirlpool Elbow